

## Common Thicknesses & Tolerances

Additional thicknesses & tolerances are available upon request

Product	Available Thickness		Thickness Tolerance	
	(inches)	(mm)	(inches)	(mm)
TLY-3, 5, 5A,5Z	0.0035	0.09		
	0.0050 (TLY-3, 5)	0.13	+/- 0.0005	+/- 0.01
	0.0100	0.25	+/- 0.0007	+/- 0.02
	0.0200	0.51	+/- 0.0020	+/- 0.05
	0.0310	0.79	+/- 0.0020	+/- 0.05
	0.0620	1.58	+/- 0.0020	+/- 0.05
TLP-5	0.0050	0.13	+/- 0.0005	+/- 0.01
	0.0100	0.25	+/- 0.0007	+/- 0.02
	0.0200	0.51	+/- 0.0020	+/- 0.05
	0.0300	0.76	+/- 0.0020	+/- 0.05
TLX-6, 7, 8, 9, 0	0.0017	0.04		
	0.0050	0.13	+/- 0.0005	+/- 0.01
	0.0100	0.25	+/- 0.0007	+/- 0.02
	0.0200	0.51	+/- 0.0020	+/- 0.05
	0.0310	0.79	+/- 0.0020	+/- 0.05
	0.0620	1.58	+/- 0.0020	+/- 0.05
TLA-6	0.0300	0.76	+/- 0.0020	+/- 0.05
	0.0570	1.45	+/- 0.0020	+/- 0.05
TLE-95	0.0015	0.04	+/- 0.0002	+/- 0.005
	0.0035	0.09	+/- 0.00025	+/- 0.006
	0.0052	0.13	+/- 0.0005	+/- 0.01
	0.0100	0.25	+/- 0.0007	+/- 0.02
TLC-30, 32	0.0200	0.51	+/- 0.0020	+/- 0.05
	0.0310	0.79	+/- 0.0020	+/- 0.05
	0.0450	1.14	+/- 0.0020	+/- 0.05
	0.0620	1.58	+/- 0.0020	+/- 0.05
RF-30-7H, RF-30 RF-30A	0.0100*	0.25	+/- 0.0007	+/- 0.02
	0.0200**	0.51	+/- 0.0020	+/- 0.05
	0.0300	0.76	+/- 0.0020	+/- 0.05
	0.0400	1.02	+/- 0.0020	+/- 0.05
EZ-IO, TSM-DS3, RF-60TC	0.0050	0.13	+/- 0.0005	+/- 0.013
	0.0100	0.25	+/- 0.0010	+/- 0.025
	0.0200	0.51	+/- 0.0020	+/- 0.05
	0.0300	0.76	+/- 0.0020	+/- 0.05
TLF-35A	0.0100	0.25	+/- 0.0010	+/- 0.025
	0.0200	0.51	+/- 0.0020	+/- 0.05
	0.0300	0.76	+/- 0.0020	+/- 0.05
	0.0600	1.52	+/- 0.0020	+/- 0.05

Product	Available Thickness		Thickness Tolerance	
	(inches)	(mm)	(inches)	(mm)
RF-35	0.0100	0.25	+/- 0.0007	+/- 0.02
	0.0200	0.51	+/- 0.0020	+/- 0.05
	0.0300	0.76	+/- 0.0020	+/- 0.05
	0.0600	1.52	+/- 0.0020	+/- 0.05
RF-35A2 RF-35TC	0.0050	0.13	+/- 0.0005	+/- 0.013
	0.0100	0.25	+/- 0.0010	+/- 0.025
	0.0200	0.51	+/- 0.0020	+/- 0.05
	0.0300	0.76	+/- 0.0020	+/- 0.05
RF-41	0.0600	1.52	+/- 0.0020	+/- 0.05
	0.1250	3.18	+/- 0.0035	+/- 0.09
RF-43	0.0100	0.25	+/- 0.0010	+/- 0.025
	0.0200	0.51	+/- 0.0020	+/- 0.05
	0.0300	0.76	+/- 0.0015	+/- 0.04
	0.0620	1.58	+/- 0.0020	+/- 0.05
	0.1250	3.18	+/- 0.0035	+/- 0.09
RF-45	0.0200	0.51	+/- 0.0020	+/- 0.05
	0.0310	0.79	+/- 0.0020	+/- 0.05
	0.0620	1.58	+/- 0.0020	+/- 0.05
TRF-43	0.1250	3.18	+/- 0.0035	+/- 0.09
	0.0080	0.20	+/- 0.0010	+/- 0.025
	0.0320	0.81	+/- 0.0020	+/- 0.05
	0.0640	1.63	+/- 0.0035	+/- 0.09
RF-10	0.1200	3.05	+/- 0.0049	+/- 0.125
	0.0100	0.25	+/- 0.0010	+/- 0.025
	0.0250	0.64	+/- 0.0020	+/- 0.05
	0.0300	0.76	+/- 0.0020	+/- 0.05
	0.0500	1.19	+/- 0.0030	+/- 0.08
	0.0600	1.58	+/- 0.0030	+/- 0.08
	0.1250	3.18	+/- 0.0040	+/- 0.10

Standard Sizes (Additional Sizes Available)			
Typical Size		Long Laminates	
Inches	mm	Inches	mm
36 W x 48 L	914 W x 1220 L	36 W x 60 L 36 W x 76 L 36 W x 102 L	914 W x 1524 L 914 W x 1930 L 914 W x 2590 L

All reported values are typical and should not be used for specification purposes. In all instances the user shall determine suitability in any given application. The above information creates no express or implied warranties.

### North & South America

Taconic - Headquarters  
136 Coonbrook Road  
Petersburgh, NY 12138  
Tel: 518-658-3202 / 1-800-833-1805  
addinfo@4taconic.com

### Europe/Middle East/Australia

Taconic International Ltd.  
Republic of Ireland  
Tel: +353-44-9395600  
add@4taconic.com

### Asia

Korea Taconic Company  
Republic of Korea  
Tel: +82-31-704-1858  
sales@taconic.co.kr

### China

Taconic Advanced Material (Suzhou) Co., Ltd.  
Suzhou City, China  
Tel: +86-512-6286-7170  
tssales@taconic.co.kr

